



**SPIRIT
MAIN SPECIFICATIONS**

Applications	Retail lighting
Optics	Diffused optics
Colour temperature	02: Warm White 3,000K; 08: Neutral White 4,000K
CRI and colour difference (SDCM)	CRI 80 Color difference among several devices: Max. 5 step MacAdam
Photobiological compliance	Exempt Group
Insulation class	Class I
Protection rating	IP20
Cable harness	N.a.
Dimensions	1195x295x10.5 mm
Weight	1.5 kg

ELECTRICAL SPECIFICATIONS

Rated voltage	220-240 V 50/60 Hz
LED current	N.a.
Power factor	> 0.9 (full load)
Control technology	Optional power supplies with DALI interface
Connection	Neoprene cable
LED life expectancy (T_{amb} -10°C to 35°C)	L70 B50 > 30,000 hr

MATERIALS

Mounting	Surface mounting; Suspension kit and Ceiling mounting kit available
Frame	Painted aluminum
Optics	N.a.
Screen	Flat polycarbonate

ACCESSORI

PSU00431	TRIAC 30W power supply
PSU00461	30W 0-10V power supply
PSU00462	60W 0-10V power supply
PSU00390	DALI 30W power supply
PAR03571	FRAME 30x120 for ceiling mounting
PAR03835	Emergency kit
ACL00085	Suspension kit

INPUT POWER AND DEVICE FLUX*
(T_{amb}=25°C, T_l=85°C, T_c=4000K)

Spirit 1	30 W	3,000 lm
-----------------	------	----------

* Values shown represent effective output flux. These values may differ from the LEDs nominal flux.

CODING

product code	LED colour	power	model code
SPRR	02	0 (N.a.)	1
	08	D (Dali)	

Product specifications may vary at any time and will be confirmed at time of order.
Values shown are calculated with +/- 5% tolerance.